

FONIX FP35 *Touch* Hearing Aid Analyzer SPECIFICATIONS

ACOUSTICAL OUTPUTS

Frequencies:	200-8000 Hz in 100 Hz intervals (user interface) 200-8000 Hz in 1 Hz intervals (RS232)
Frequency Accuracy:	1%.
Amplitudes:	40-100 dB in 5 dB intervals coupler, 40-90 dB in 5 dB intervals real-ear (user interface) 40-100 dB in 0.01 dB intervals coupler, 40-90 dB in 0.01 dB real-ear (RS232)
Accuracy:	Coupler: ± 2.5 dB from 300 to 5000 Hz, all others ± 3.5 dB (after leveling) Real-ear: ± 3 dB, 200-8000 Hz (after leveling)
Distortion (at 70 dB SPL):	Puretone: $< 0.5\%$, 400-2500 Hz

TELECOIL OUTPUTS

Field Strength:	TMFS, 1, 1.78, 3.16, 5.62, 10, 17.8, 31.6, 56.2, 100 mA/m (user interface) 0-180 mA/m in 0.01 mA/m specified intervals (RS232)
Accuracy:	± 2 dB

DIGITAL READOUT OF SOUND PRESSURE LEVEL

Frequency Range:	200-8000 Hz
Amplitude Range:	0-150 dB SPL
Resolution:	0.1 dB
Accuracy:	Coupler measurements: ± 2.0 dB Probe measurements: ± 2.0 dB Reference measurements: ± 2.0 dB
Equivalent Input Noise:	< 50 dB RMS

MEASUREMENT INPUTS

Probe Microphone:	Crosstalk from reference microphone: < -80 dB Crosstalk from coupler microphone: < -80 dB
Reference Microphone:	Crosstalk from probe microphone: < -80 dB Crosstalk from coupler microphone: < -80 dB

HARMONIC DISTORTION ANALYZER

Type	2nd, 3rd, and Total (2nd + 3rd)
Resolution:	0.1 %

AVAILABLE TESTS

Automated test sequences:	ANSI S3.22-1996, ANSI S3.22-2003, IEC 60118-7:1994, JIS:2000, ISI
Additional Coupler Test:	Coupler Multicurve, Coupler Target, Coupler EarSim
Real-ear Test Screens:	Audiogram Entry, Insertion Gain, Real-ear Unaided & Aided, Real-ear SPL

INPUT POWER

Voltage:	100 - 240 volt AC
Frequency Range:	47 - 63 Hz
Current:	1.35A
Power dissipation:	27 watts typical with full operation. 23 watts when unit is in Standby.
Earth Leakage current:	< 500 uA
Patient Leakage current:	< 100 uA

PHYSICAL DIMENSIONS

Net Size:	16 x 11 x 4.9 inches
Net Weight:	12 lbs (5.45 Kg) with softcase and all accessories (except manual)
Touch Screen:	Resistive

INTERNAL PRINTER

Type:	Thermal
Paper width:	80 mm (+0, -1 mm)

EXTERNAL PRINTER

Interface:	Parallel
Language:	HP PCL3

INTERNAL SOUND CHAMBER DIMENSIONS

Test area:	2.65" W x 5.25" L x 1.1" H
Speaker:	2.5" cone

ENVIRONMENTAL CONDITIONS

Operating Conditions:	15 - 35° C (59 - 95° F), 5-85% humidity (non-condensing)
Shipping Conditions:	-20 - 60° C (-4 - 140° F), 5-85% humidity (non-condensing)



FRYE ELECTRONICS, INC.

P.O. Box 23391 • Tigard, OR 97281-3391 • USA
(503) 620-2722 • (800) 547-8209
Fax: (503) 639-0128
www.frye.com • email: sales@frye.com