Steps to add ASNI 2014 to FONIX 8000 Opening Screen



On Fonix 8000 front panel, open Setup Menu screen with General Default Settings

Use the Down Arrow to choose down to F7

			FONI	8000 TI Setup	EST S Menu	YSTEM				
		General Default Settings								
		Fint Label - rinter xt Prnt Colo xt Prnt Lang xt Prnt #Scr S232 Baudraf hid Type Jser start Screen	Printer Juage rns/Page tisc te Be C	Off iternal B&W HPCL 1 - 57600 Linear ginner Ipening	Swee Swee Misc I/O I/O Rese Avg	Nelay P Strt Dela P Meas Dela Start Delas Meas Delay Meas Delay t Freq Freqs	<u>is/Tone</u> yy Defa yy Defa Defa Defa Defa NFA 25	ult ult ult ult ult Joo 500		
-		<u>Open</u> 4 5 6 7	ing Screen - ANSI 53,2 Pr ANSI	22 2003 None rofiler 53.42	Pres defa	s F1 for add ult settings	ditional S.			
Use START and UP,	/DOWN to	o select iter	n. Use LEFT	/RIGHT t	o chai	nge item.			LEV	ELED
Press Function K	ey to p F2	erform that a	action.	1 .55		FC	F 7	E	init	ializing
Settings F Selection Mo	ind dules	Set Time/Date	14	Sav Cham L	e evel	Calibrate Microphones	Load Setup Defaults	Save S Defau	etup lts	2022-10-25 9:06:56AM



Press RIGHT Arrow until selection reads: ANSI S3.22 2014

Press EXIT. ANSI S3.22 2014 is now on the Opening Screen.

